

iRo

Interactive Flat Panel Display

TYPE H





Interactive Flat Panel Display

TYPE H



ZeroBonding

Excellent writing experience, around 1mm gap between cover glass and open cell.

See more clearly hear more really

Built-in 13 Mega pixel **camera** and 8 array **microphones**, 3 cavities, 2 full-frequency, 1 treble output, creating the ultimate audio-visual experience.

Multiple optional built-in modules

Built-in camera, NFC, Light/Temperature sensor.

Colorful display, Extraordinary vision

Full-scene 4K UI, beautiful colors, realistic rendering of the scene.

TYPE H





TYPE H



Sharing multiple devices at the same time to encourage effective collaboration



Wireless sharing from your device#BYOD

**Free annotation
without worrying
ink-spilled
on unlimited
pages**



Specification

		IR65H	IR75H	IR86H
PANEL FEATURES	Panel type/backlight	LCD/DLED		
	Aspect ratio	16:9		
	Refresh rate	60 hz		
	Contrast ratio	1200:1		
	Life time	50000H		
	Resolution	3840(H) x 2160(V)		
	Display color	1.07 Billion colors		
	Brightness	500 cd/m ²		
	View angle	R/L 178 (Min.), U/D 178 (Min.)		
SOUND/SPEAKER FEATURE	Speaker type	2pcs Built-in, Left/Right		
	Speaker output	2x 20 watt		
INPUTS	HDMI input	4x HDMI		
	Multi-Media USB	4x USB 3.0, 2x USB 2.0		
	RS232	1x		
	RJ-45	2x		
	Type-C input	2x type C output display		
	Built in camera	Yes with 13MP 4K Resolution & 8 Array Microphone		
OUTPUTS	HDMI output 2.1	1x		
UTS	Bluetooth / WIFI	Bluetooth 5.2 / Wifi 6		
	Touch input	2x USB type B		
TOUCH SCREEN	Cover glass	4mm Toughened, 8 Mohs, Anti-glare		
	Touch tech parameters	Infrared touch		
	Touch accuracy	1mm		
	Responses time	<5ms		
	Compatibility	Windows/ Linux/ Mac/ Android/ Chrome		
	Touch Point	40 points		
ANDROID	OS Version	Android 13		
	Storage	64 GB + 256 GB		
	RAM	8 GB		
WALL MOUNT		VESA Standard		
INPUT VOLTAGE		AC:100 240V 60/50HZ		
POWER RATE		≤230W	≤300W	≤400W
STANDBY		≤0.5W		
ENVIRONMENTAL FACTORS		Working Temperature : 0° - 40°		
		Working Humidity 10% - 80%		
STRUCTURAL INFO	(W*H*D) mm	1486*909*89.9	1707*1034*90.6	1953.96*1173.62*90.6
	N.W (kg)	40	55	67